














Prism Type	Image 1	Image 2	Absolute Prism Constant for: Nikon, Pentax, Sokkia, Topcon, Trimble	Leica Prism Constant
<b>GD-PR1</b> (Silver or Copper)			-34.4	0.0
<b>GD-PR111</b>			-34.4	0.0
<b>GD-PR121</b> (Silver or Copper)			-34.4	0.0
<b>Retro-reflective tape</b>	25x25mm 	40x40mm 	0.0	+34.4
<b>GD-LBAR</b> (Silver or Copper)			-25.4	+9.0
<b>GD-DLBAR</b> Dual L-bar prism (Silver or Copper)			-25.4	+9.0

Prism Type	Image 1	Image 2	Absolute Prism Constant for: Nikon, Pentax, Sokkia, Topcon, Trimble	Leica Prism Contant
GD-GMP101			-16.9	+17.5
GD-YMP (Silver or Copper)			-16.9	+17.5
GD-RMP-175C			-16.9	+17.5
GD-RMP-0C			-34.4	0.0
GD-RMP-0ABS Reversible 0 / -30mm (absolute)			0.0 / -30.0	+34.4 / +4.4
GD-360MP (Mini 360°)			-6.0	+28.4

Prism Type	Image 1	Image 2	Absolute Prism Constant for: Nikon, Pentax, Sokkia, Topcon, Trimble	Leica Prism Constant
<b>GD-360-4</b> (Large 360°)			<b>-11.3</b>	<b>+23.1</b>
<b>46-1450</b> (30 mm ball monitoring prism)			<b>-11.3</b>	<b>+23.1</b>
<b>46-1445</b> (38.1 mm ball monitoring prism)			<b>-16.9</b>	<b>+17.5</b>
<b>46-BRT-K</b> (Bireflex Target)			<b>+2.0</b>	<b>+36.4</b>
<b>GD-GPR112</b> Monitoring prism			<b>-41.4</b>	<b>-7.1</b>